

BOULEVARD runners

Manufacturing process	Tufted		ISO 2424
Gauge	5/32" Loop		
Pilecomposition	100% PP		ISO 2424
Primary backing	Woven PP		ISO 2424
Secondary backing	ECO Grip Felt		ISO 2424
Width	67 cm, 80 cm, 100 cm	± 1%	EN 986
Pile weight	ca. 420 gr/m ²		ISO 8543
Total weight	Gel ca. gr/m ²	ECO Grip Felt ca. 1490 gr/m ²	± 15% ISO 8543
Pile height	ca. 4,0 mm		ISO 1765
Total height	Gel ca. mm	ECO Grip Felt ca. 6,5 mm	+ 15% / -10% ISO 1765
Number of knots	ca. 115.920 /m ²		+ 10% / -7,5% ISO 1763
Fire classification	ECO Grip Felt Efl (EN13501-1)		EN 13501-1
Light fastness	5		105-B02
Wearability	≥ 4		105-X12
Water fastness	≥ 4		105-E01
Thermal resistance	0,120 m ² K/W		ISO 8302
Sound insulation	10,0 dB		ISO 10140
GUT Nr.	Gel	ECO Grip Felt 2FAE5168	

Floorsymbols ECO Grip Vlies



Certificates

